



### Category 5e Unshielded RJ-45 Keystone Jacks

Transmission and Electrical Specifications									Typical Return Loss (Forward, Component Level)	
Frequency	Insertion Loss		NEXT		FEXT		RL			
MHz	dB		dB		dB		dB			
	Nom	Max	Nom	Min	Nom	Min	Nom	Min		
1.00	0.02	0.10	85.0	65.0	77.0	65.0	55.0	30.0		
4.00	0.03	0.10	75.0	65.0	65.0	63.1	50.0	30.0		
8.00	0.04	0.11	70.0	64.9	60.0	57.0	48.0	30.0		
10.00	0.04	0.13	68.0	63.0	58.0	55.1	42.0	30.0		
16.00	0.05	0.16	64.0	58.9	54.0	51.0	40.0	30.0		
25.00	0.06	0.20	60.0	55.0	50.0	47.1	35.0	30.0		
31.25	0.07	0.22	58.0	53.1	48.0	45.2	33.0	30.0		
62.50	0.11	0.32	52.0	47.1	42.0	39.1	28.1	24.1		
100.00	0.15	0.40	45.0	43.0	38.0	35.1	24.0	20.0		


Propagation Delay	2.5 nS max @ 1-100 MHz
Propagation Delay Skew	1.25 nS max @ 1-100 MHz
Current rating	1.5 A max.
Contact resistance	20 mOhm max (per contact)
Input/Output resistance	200 mOhm max
Input/Output resistance Unbalance	50 mOhm max
Voltage rating	72 Vdc max
Dielectric strength	1000 Volts rms for 1 minute
Insulation Resistance	500 MegaOhm min @ 500 Vdc
DC Resistance	0.1 Ohm max @ 20C
TCL	28-20-Log(f/100) dB min @ 1-100 MHz
Transfer Impedance	N/A

#### Typical Test Results at the Component Level

Worst PS-NEXT



Typical Insertion Loss



#### Ordering Information

HCS P/N	Description	Termination Blocks	Punch-Down Tool	T568
J5E-00811	8P8C RJ-45 Unshielded Keystone Jack CAT 5e	110 IDC	110	B
J5E-00812	8P8C RJ-45 Unshielded Keystone Jack CAT 5e	110 IDC	110	A
J5E-00813	8P8C RJ-45 Unshielded Keystone Jack CAT 5e	110 IDC	110	UNI
J5E-00814	8P8C RJ-45 Unshielded Keystone Jack CAT 5e	110 IDC	LSA Plus & 110	B
J5E-00815	8P8C RJ-45 Unshielded Keystone Jack CAT 5e	110 IDC	LSA Plus & 110	A
J5E-00816	8P8C RJ-45 Unshielded Keystone Jack CAT 5e	110 IDC	LSA Plus & 110	UNI
J5E-00817	8P8C RJ-45 Unshielded Keystone Jack CAT 5e	110 IDC	LSA Plus & 110	UNI